




glasswashers

# C Range | undercounter



- **2 year warranty**
- C405 WS with manual internal regeneration water softener & drain pump as standard
- Four button bright LED display with soft touch controls, twin traffic lights giving instant status updates & operational self-diagnostics
- Alarms menu with hi-level information retrieval
- Improved wash action from quick release parallel wash & rinse arm design
- Surface scrap tray filters supplied as standard
- Fitted drain pump version available on C352, C402, C452 & C502\*
- Three standard cycle time options with further options available
- Cycle times can be tailored to site requirements
- Automatic self-cleaning at end of service
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Patented dual flow wash pump (excluding C352) – reducing power consumption whilst retaining wash efficiency
- Moulded wash tank for easy cleaning (excluding C452)
- Moulded rack guide giving partial double skin (excluding C452)
- Accurate detergent & rinse aid peristaltic dosing pumps as standard
- Supplied with two open cup/glass racks & cutlery insert



**NEW four button bright LED display with soft touch controls & twin traffic lights giving instant status updates**

## Technical

- Standard voltage 230V – single phase
- C502 can be supplied 3 phase – **please specify at time of order**
- Suitable for hot (max 50°C) or cold water supply, typically at 2 to 4 bar dynamic supply pressure, refer to specification sheets for individual requirements
- Wash temperature 60°C (adjustable)
- Rinse temperature 65°C (adjustable)
- Cycle times between 70 & 240 secs, dependent on model

\* Drain pump cannot be retro fitted to C502.

Drain pump versions require a waste up stand for correct operation.

Restrictive waste connections should be avoided for all installations.

All machines supplied 13 amp will come with moulded plug and cable.

Machines configured for 13 amp supply or fitted to cold water supply will not be capable of running repeated short cycles. The cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required
<b>C352</b>	350	240	400 x 495 x 590†	3 Cycles	2.8	13
<b>C352D</b>			As C352 above with fitted drain pump			
<b>C402</b>	390	300	440 x 540 x 670†	3 Cycles	2.8	13
<b>C402D</b>			As C402 above with fitted drain pump			
<b>C405 WS</b>	390	300	440 x 540 x 670†	3 Cycles	2.8	13
<b>C452</b>	450	280	525 x 560 x 705†	3 Cycles	2.8	13
<b>C452D</b>			As C452 above with fitted drain pump			
<b>C502*</b>	500	340	580 x 610 x 810#	3 Cycles	2.6/4.5/6.5	13/20/30##
<b>C502D</b>			As C502 above with fitted drain pump			

† Height excludes adjustable feet which will add 5 to 15mm. # Height excludes adjustable feet which will add 10 to 20mm.

## Machines will be supplied for 30 amp supply as standard. If supplied 13 amp machine will come fitted with moulded plug and cable.

20 amp machines will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

See page 11 for ancillary items.